

NationalLED

SecureLight Hazardous Location

Project

Date

Catalog Number

Type



HAZARDOUS LOCATION



HAZARDOUS LOCATION



Specifications

Construction

- Weather resistant, corrosion free construction.
- Housing constructed of white UL 5VA fiberglass with an F1 Weatherability rating.
- Poured-in-place gasket and cam latches seal the enclosures from most hostile environments.
- Knockouts and end plugs provided for easy wiring access.
- Diffuser is 100% impact resistant acrylic secured to housing with clear cam latches standard (optional stainless steel available).

Electrical

- Voltage: 120-277V or 347-480V AC input
- Driver: Class 2, constant current, calibrated to lumen package (0-10V dimming standard)

Mounting

- Surface mount, single loop adjustable cable, and chain hang ready.
- Pendant mount option available

Controls

- Consult factory for control options

Warranty

- Standard 5-year limited warranty.
- 10-year Optional

ORDERING GUIDE

Example: SLHL 2 2000L 30K RFA DIM SRG HL

Fixture Type	Size	Model	CCT	Lens/Optics	Driver	Options	Hazardous Location
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
SLHL Hazardous Location	2 2 FT	2000L	30K 3000K	RFA Ribbed Frosted Acrylic SFA Smooth Frosted Acrylic	DIM Dim 0-10V, 120-277V	SRG 20kA Surge Protector PND Pendant Mount 45B 45" Bracket Mount SSL Stainless Steel Latches SST Tamper Proof Screws with Stainless Steel Latches	HL Hazardous Location
		3500L	35K 3500K				
		4000L	40K 4000K				
	4 4 FT	3500L	50K 5000K				
		4000L					
		5000L					
		6000L					
	8 8FT	8500L					
		5000L					
		6000L					
		8500L					
		10000L					

SLHL

www.NationalLED.com | 832-459-4447


Due to continued product improvements, product specifications are subject to change without notice. Please visit www.NationalLED.com for the most updated product specifications.

Performance Data

SIZE	MODEL	CCT	LENS/OPTICS	LUMENS	WATTAGE	EFFICACY
4 ft	3500L	4000K	SFA	3371	25.6	131.7
	4000L		SFA	4319	34.7	124.5
	5000L		SFA	5268	44.4	118.6
	6000L		SFA	6002	54.4	110.3

ISO Lines

SMOOTH
FROSTED



Dimensional Data

Standard Sizes

